


This electronic collection of documents is provided for the convenience of the user and is Not a Certified Document –


The documents contained herein were originally issued and sealed by the individuals whose names and license numbers appear on each page, on the dates appearing with their signature on that page.


This file or an individual page shall not be considered a certified document.


























(LOOKING AT EXPOSED FRONT FACE OF MSE RETAINING WALL)


DATE: 9-17

DATE: 9-17

- DS GEU

PREPARED BY: R. WEBB

REVIEWED BY: G. BODENHEIMER





NORTH CAROLINA DEPARTMENT OF TRANSPORTATION **DIVISION OF HIGHWAYS**

GEOTECHNICAL ENGINEERING UNIT GUILFORD COUNTY

MSE ABUTMENT WALLS PLAN AND ELEVATION VIEW SITE 6 WALL 6A END BENT 1

REVISIONS					SHEET
BY	DATE	NO.	BY	DATE	NO.
		3			W-9
		4			V V-3





ELEVATION - END BENT 2

(LOOKING AT EXPOSED FRONT FACE OF MSE RETAINING WALL)

PROJECT NO.: U-2525C

GUILFORD COUNTY

STATION: 470+43.12 -L- & 24+51.12 -Y6-

SHEET 10 OF 13

NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS

GEOTECHNICAL
ENGINEERING UNIT

MSE ABUTMENT WALLS
PLAN AND ELEVATION VIEW
SITE 6 WALL 6B
END BENT 2

 REVISIONS

 D.
 BY
 DATE
 NO.
 BY
 DATE
 NO.

 1
 3
 W-10


 2
 4
 W-10


PREPARED BY: R. WEBB

DATE: 9-17

REVIEWED BY: B. BODENHEIMER

DATE: 9-17





DESIGN TABLE MINIMUM FOUNDATION NOMINAL NOMINAL FACTORED FOOTING FRICTION REINFORCEMENT FOOTING VERTICAL LENGTH LIVE LOAD DEAD LOAD ANGLE PRESSURE LB/SF LB/SF LB/SF DEGREES FEET MSE WALL 1A 700 30 25 8000 2600 MSE WALL 1B 2750 700 28 8500 MSE WALL 2A 7500 600 30 26 8000 MSE WALL 2B 2500 600 30 27 MSE WALL 4A 32 2300 600 8000 MSE WALL 4B 2300 600 30 24 7000 MSE WALL 5A 650 28 29 7000 2300 MSE WALL 5B 30 23 7000 2350 MSE WALL 6A 23 3100 800 7500 3100 800 30 7500 MSE WALL 6B 24

SELECT MATERIAL QUANTITIE			
MSE ABUTMENT WALL NO.5B	2300 TONS		
TOTAL	2300 TONS		

GEOTEXTILE FOR STABLIZATION QUA	
MSE ABUTMENT WALL NO.5B	1000 SQYDS
TOTAL	1000 SQYDS

ESTIMATED MSE WALL QUANTITIES (square feet)				
MSE ABUTMENT WALL NO.1A	3100 SF			
MSE ABUTMENT WALL NO.1B	3900 SF			
MSE ABUTMENT WALL NO.2A	4700 SF			
MSE ABUTMENT WALL NO.2B	5200 SF			
MSE ABUTMENT WALL NO.4A	4400 SF			
MSE ABUTMENT WALL NO.4B	4200 SF			
MSE ABUTMENT WALL NO.5A	3600 SF			
MSE ABUTMENT WALL NO.5B	3200 SF			
MSE ABUTMENT WALL NO.6A	4300 SF			
MSE ABUTMENT WALL NO.6B	4800 SF			
TOTAL	41,400 SF			

PREPARED BY: R. WEBB DATE: 11-17 REVIEWED BY: G. BODENHEIMER DATE: 11-17

NOTES:

- 1. DEFINE MECHANICALLY STABILIZED EARTH (MSE) ABUTMENT WALLS AS RETAINING WALLS 1A, 1B, 2A, 2B, 4A, 4B, 5A, 5B, 6A, AND 6B.
- 2. FOR MSE ABUTMENT WALLS, SEE MECHANICALLY STABILIZED EARTH ABUTMENT WALLS PROVISION.
- 3. FOR TYPE III REINFORCED BRIDGE APPROACH FILL, SEE BRIDGE APPROACH FILLS PROVISION AND ROADWAY DETAIL DRAWING NO. 422D10.
- 4. A SEPARATION GEOTEXTILE IS REQUIRED AT THE BACK OF THE REINFORCED ZONE FOR MSE ABUTMENT WALLS.
- 5. A DRAIN IS REQUIRED FOR MSE ABUTMENT WALLS.
- 6. DESIGN MSE ABUTMENT WALLS FOR THE FOLLOWING: 1) H = DESIGN HEIGHT + EMBEDMENT
- 2) DESIGN LIFE = 100 YEARS
 3) MAXIMUM FACTORED VERTICAL PRESSURE ON FOUNDATION MATERIAL ACCORDING TO THE DESIGN TABLE
 4) WITHIN HORIZONTAL LIMITS OF FOOTING LOADS, MINIMUM REINFORCEMENT LENGTH (L) ACCORDING TO THE DESIGN TABLE
 5) OUTSIDE HORIZONTAL LIMITS OF FOOTING LOADS, MINIMUM REINFORCEMENT LENGTH (L) = 0.7 H
- 6) DESIGN PARAMETERS:

OF DESTON T ANAMETERS:					
MATERIAL TYPE	UNIT WEIGHT (g) LB/CF	FRICTION ANGLE (f) DEGREES	COHESION (c) LB/SF		
REINFORCED ZONE	110	38	0		
RETAINED ZONE	120	30	0		
FOUNDATION	120	SEE DESIGN TABLE	0		

- 7. SEE THE WALL ELEVATION FOR THE HORIZONTAL LIMITS OF FOOTING LOADS ALONG THE WALL FACE.
- 8. SEE STRUCTURES PLANS FOR FOOTING DIMENSIONS.
- 9. SEE FIGURE 6-2 AND ASSOCIATED COMMENTARY FROM 6.1.1 FHWA-NHI-10-024 FOR DESIGN OF MSE ABUTMENT WALLS.
- 10. WITHIN HORIZONTAL LIMITS OF FOOTING LOADS, USE ACTIVE ZONE ACCORDING TO FHWA FIGURE 6-2, AND USE "F*X" AT 20 FEET FOR ALL ELEVATIONS, AND ADJUST Kr/Ka ACCORDING TO FHWA.
- 11. USE THE SAME SOIL REINFORCEMENT DESIGN FOR ALL AREAS SUBJECT TO FOOTING LOADS.
- 12. USE THE CONNECTION REQUIRED AT THE TOP REINFORCEMENT LEVEL BELOW THE FOOTING FOR ALL CONNECTIONS SUBJECT TO FOOTING LOADS.
- 13. REINFORCEMENT MUST BE MORE THAN ONE FOOT FROM THE END BENT FOOTING.
- 14. DESIGN MSE ABUTMENT WALLS FOR A NOMINAL UNIFORM LIVE LOAD (TRAFFIC) SURCHARGE OF 240 PSF.
- 15. DESIGN MSE ABUTMENT WALLS FOR BRIDGE FOOTING LOADS. USE THE NOMINAL FOOTING LIVE LOAD AND NOMINAL FOOTING DEAD LOAD FOUND ON THE DESIGN TABLE.
- 16. AFTER CONSTRUCTING MSE ABUTMENT WALLS, AND BEFORE CONSTRUCTING FOOTING, OBSERVE A ONE MONTH WAITING PERIOD. SEE SURCHARGE WALL PLANS FOR ADDITIONIAL WAITING PERIODS FOR WALLS 2A AND 2B.
- 17. COORDINATE WITH BRIDGE CONTRACTOR TO CONSTRUCT VERTICAL COPING FOR MSE ABUTMENT WALLS.
- 18. DO NOT PLACE LEVELING PAD CONCRETE, AGGREGATE OR REINFORCEMENT FOR MSE ABUTMENT WALLS UNTIL EXCAVATION DIMENSIONS AND FOUNDATION MATERIAL ARE APPROVED.
- 19. DESIGN REINFORCEMENT FOR MSE ABUTMENT WALLS TO AVOID CONFLICTS WITH FOOTINGS FOR END BENTS. SEE STRUCTURES PLANS FOR FOOTING LOCATION AND ELEVATION.
- 20. AT THE CONTRACTOR'S OPTION, "TEMPORARY SHORING FOR WALL CONSTRUCTION" MAY BE USED TO CONSTRUCT MSE AUBUTMENT WALLS. SEE MSE AUBUTMENT WALLS PROVISION FOR TEMPORARY SHORING FOR WALL CONSTRUCTION.
- 21. EXISTING OR FUTURE OBSTRUCTIONS SUCH AS GUARDRAIL, FENCE OR HANDRAIL POSTS, PAVEMENTS, PIPES, INLETS OR UTILITIES MAY INTERFERE WITH REINFORCEMENT FOR MSE ABUTMENT WALLS.
- 22. BEFORE BEGINNING WALL DESIGN FOR MSE ABUTMENT WALLS, VERIFY WALL LOCATION INCLUDING LOCATION OF BRIDGE WINGWALLS. IF NECESSARY, SUBMIT A REVISED WALL PLAN AND PROFILE VIEW (WALL ENVELOPE) FOR REVIEW. DO NOT START WALL DESIGN OR CONSTRUCTION UNTIL THE REVISED WALL ENVELOPE IS ACCEPTED.
- 23. FOR CONCRETE DITCHES, SEE SECTION 850 OF THE STANDARD SPECIFICATIONS.
- 24. UNDERCUT FOR MSE WALLS IS EXPECTED TO BE REQUIRED AT WALL 5B OVER THE LIMITS SHOWN ON THE ELEVATION VIEW FOR THE ENTIRE FOOTPRINT OF THE WALL. SEE MECHANICALLY STABILIZED EARTH ABUTMENT WALLS PROVISION.

PROJECT NO.: U-2525C

SHEET 13 OF 13

GEOTECHNICAL ENGINEER

SEAL 028669

11/15/2017

DOCUMENT NOT CONSIDERED FINAL

UNLESS ALL SIGNATURES COMPLETED

Scott Webb

----5A62DE9561AC4D6...

ENGINEER

GUILFORD COUNTY STATION:


NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION


GEOTECHNICAL ENGINEERING UNIT


DIVISION OF HIGHWAYS


MSE ABUTMENT WALLS NOTES

REVISIONS						SHEET
Ο.	BY	DATE	NO.	BY	DATE	NO.
			3			W-13
:			4			V V-13









NOTES:

FOR SOIL NAIL RETAINING WALLS, SEE SOIL NAIL RETAINING WALLS PROVISION.

FOR SINGLE FACED PRECAST CONCRETE BARRIER, SEE ROADWAY PLANS AND SECTION 857 OF THE STANDARD SPECIFICATIONS.

BEFORE BEGINNING SOIL NAIL WALL DESIGN FOR THE SOIL NAIL WALL, SURVEY WALL LOCATION AND SUBMIT A REVISED WALL PROFILE VIEW (WALL ENVELOPE) FOR REVIEW. DO NOT START WALL DESIGN OR CONSTRUCTION UNTIL THE REVISED WALL ENVELOPE IS ACCEPTED.

DESIGN THE SOIL NAIL WALL FOR THE FOLLOWING:

1) H = DESIGN HEIGHT + EMBEDMENT

2) DESIGN LIFE = 75 YEARS


3) IN-SITU ASSUMED MATERIAL PARAMETERS:

UNIT WEIGHT, γ = 120 PCF

FRICTION ANGLE, φ = 30 DEGREES

COHESION, c = 0 PSF

FOR CONCRETE DITCHES, SEE SECTION 850 OF THE STANDARD SPECIFICATIONS



CONCRETE DITCH DETAIL

**SEE WALL ENVELOPE FOR GRADE ELEVATIONS.

***SEE PLANS FOR FINISHED GRADE DETAILS.

PROJECT NO.: U-2525C

GEOTECHNICAL

ENGINEER

Scott Webb 1/12/2018


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

ENGINEER

GUILFORD COUNTY

STATION: 22+94.5 Y6RPD TO 24+45 Y6RPD

SHEET 2 OF 2



NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS

GEOTECHNICAL ENGINEERING UNIT SOIL NAIL WALL TYPICAL SECTION AND DETAILS

 REVISIONS

 D.
 BY
 DATE
 NO.
 BY
 DATE
 NO.

 1
 3
 W-17

 2
 4
 W-17

PREPARED BY: R. WEBB

DATE: 1-18

REVIEWED BY: G. BODENHEIMER

DATE: 1-18

ACB TICB